Air King Ventilation Products®

SPECIFICATIONS

52" Ceiling Fan with Light

52" BUILDER'S CHOICE CEILING FANS WITH LIGHT
120 Volts, 0.5 amps, 60 hz.

➤ **FAN BODY**
Powder coated .0035" thick steel body housing.

➤ **MOTOR**
Permanently lubricated, powerful 3-speed reversible motor.
120 volt, 60 hz, 0.5 amp, 60 watt.

➤ **UNIT MOUNTING**
Dual mounting. Close to ceiling mounting or Downrod. All mounting hardware including a 4" downrod is included in box.

➤ **FINISHES**
9800 - Polished Brass body
9805 - White/Polished Brass body
9810 - White body
9815 - Antique Brass body

➤ **PADDLES**
9800L - 5 reversible Cherry/Oak paddles
9805L - 5 reversible White/Bleached Oak paddles
9810L - 5 reversible White/Bleached Oak paddles
9815L - 5 reversible Cherry/Dark Oak paddles

➤ **LIGHTING**
Center mounted 100 watt maximum schoolhouse light kit.
Light kit and fan are shipped in one carton. (bulb not included)

➤ **SINGLE PACK SHIPPING INFO**
➤ Box Dim 21"x $9^{13}/_{16}$"x $10^{1}/_{8}$"
➤ UPC: 9800L 0-8316237588-9
9805L 0-8316237688-6
9810L 0-8316237888-0
9815L 0-8316237988-7
➤ Shipping Weight - 15.4 lbs.

PROJECT		ARCHITECT		
LOCATION		ENGINEER		
CONTRACTOR		SUBMITTED BY		DATE

FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS

U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 1-877-304-3785
Fax: (610) 696-4648

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015

Downloaded from www.Manualslib.com manuals search engine